

Campbell®

6423000

"GX" Clamps

Bestellnr.:6423000

Standard Leadtime



### "GX" Clamps

- "GX" clamp is entirely drop forged and heat treated.
- Can be used for both vertical and horizontal-to-vertical lifting.
- Exclusive feature is a patented wear indicator system. When any of cam's straight line, convex

### Marketing Texte

Long description "GX" Clamps

Product claim

- "GX" clamp is entirely drop forged and heat treated.
- Can be used for both vertical and horizontal-to-vertical lifting.
- Exclusive feature is a patented wear indicator system. When any of cam's straight line, convex teeth are flattened between unique wear indicator grooves, it is time to change the cam.

teeth are flattened between unique wear indicator grooves, it is time to change the cam.

- Shackle and “G” link combined into one part for fewer stress points and less chance of side loading damage.
- 100% proof tested with certificate of test attached to each clamp.
- Note: The Pad and Cam should be replaced at the same time.
- Clamps are 100% Proof Tested and Certificate of Test supplied with each clamp.

- Shackle and “G” link combined into one part for fewer stress points and less chance of side loading damage.
- 100% proof tested with certificate of test attached to each clamp.
- Note: The Pad and Cam should be replaced at the same time.
- Clamps are 100% Proof Tested and Certificate of Test supplied with each clamp.

Short description “GX” Clamps

### Packaging information

Pieces per card 1

### Technical Data

Color Grey/blue

Material Steel

Surface finish Painted

Use Area Outdoor

Working load limit 0.5 metric tons

Grip range 1 - 16 mm









